LT1254RDMME

Description: Manual Oil Bucket Pump w/ Calibrated Pump Handle; w/ 30lb (13.6KG) Steel Bulk Fill Container & Curved Nozzle (self enclosed unit)

1. Include Low Pressure Manual Oil Pump

2 5FT(1.52mts) Low Pressure Oil Delivery Hose

3. 6" Curved Nozzle Assembly with Non-Drip Nozzle.

4. Optional Attachment: 6" Straight Nozzle Assembly with Non-Drip Nozzle

5. Calibrated to deliver approximately 125 milliliters per stroke; Output: 8 strokes delivers 1 Liter of Oil; 1 pint per 7 strokes using SAE90 Gear Lubricant at 70 degrees F.

6. Lube Outlet: 1/2"NPT(f)

7. Steel Container Size: 16"(40.6CM) High by 9 1/2"(24.1CM) Diameter Painted in Red (Bulk Filled Unit)

8. Pump Specifications: Pump Tube Length 17.0"(43.2CM) and Diameter: 1-5/8"(4.13CM); Overall Height: 26.0"(66.04CM)

9. 3 Rigid Steel Clamps that clamp the cover firmly in place on the container

10. Steel Drum Cover with screws that firmly fasten the cover to the base of the pump.

11: Easy 4-1/4"(10.8CM) Carry Handle welded to the side of the container makes for easy transportability

12. 4"(10.2CM) Welded Foot Support (welded to the base of the container) for additional pumping leverage.

13. 16-1/2"(40.6CM) Long x 1"(2.54CM) Diameter Solid Cast Pump Handle for long strokes and pumping leverage. Stroke Length: 3-1/4"(8.3CM)

14. One year Warranty against Defective Materials, Workmanship and Labor

15. Replacement and Repair Parts Available.

16. Other Information: Weight and Dimensions:

e: http://www.iserv.net/~wmogrady/lube.html

BOX Weight: 32LBS (9.98KG)

BOX Dims: Length: 30.5"(77.5cm) X Width:14.5" (36.9cm) X Height: 13"(33.1cm)

WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY P.O. BOX 456; ADA, MI. 49301 USA TEL: 616-676-1792; FAX: 616-676-1287 Contact: willmarllc@gmail.com

"Doing Business with the World"

WILLMARLUBE P.O. BOX 456; ADA, MI. 49301 USA TEL: 616-676-1792; FAX: 616-676-1287 Contact: sales@willmarlube.com Website: http://www.willmarlube.com

