

## LT3050ME

### High Pressure High Volume Grease Control Valve

#### DESCRIPTION

Control Valve for Grease(3/8"NPT(f)) w/ High Pressure Coupler LT5845ME; For use with all Air Operated High Pressure Grease Pumps; Grease Inlet: 3/8" NPTF; Operating Pressure 7500PSI; 6"(15.24CM) Solid Flexed Extension Tube with 1/8"NPT (m) Thread  
Includes High Pressure 7500 PSI Zerk Coupler (LT5845ME)  
Grease Inlet 3/8" NPT (f)  
Repair Kit: R82157ME  
For Use with all Air Operated High Pressure Grease Pumps  
Can be used with PSI Approved Spring Loaded Grease Hose Attachment

**Complete Repair Kits and Parts Available**

**Other Information: Weight and Dimensions:**

BOX Weight: 2LB(.92KG)

BOX Dimensions: Length: 9.0"(22.9cm) X Width:3-

1/2"(8.9cm) X Height: 1-1/2"(3.8cm)



**WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY**

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: [willmarllc@gmail.com](mailto:willmarllc@gmail.com)

Website: <http://www.iserv.net/~wmograde/lube.html>



"Doing Business with the World"

**WILLMARLUBE**

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: [sales@willmarlube.com](mailto:sales@willmarlube.com)

Website: <http://www.willmarlube.com>