LT500ME

Description: High Pressure Manual Grease Pump with Cover for 55 gallon / 400 lb Refinery Container. ***(follower plate not included)***

1. Includes High Pressure Manual Grease Pump
2 5FT(1.52mts) X 1/4" High Pressure Grease 3260 PSI Delivery Hose
3. High Pressure Grease Coupler (LT5852ME)
4. Develops a Max Pressure of 3500 LBS(PSI)
5. Lube Outlet: 3/8"(f)NPT
6. Steel Drum Cover Painted in Bright Red, made of 1/8" solid heavy duty plate steel . Diameter to fit a standard 400LB (55 Gallon) Refinery Drum; Cover ID: 24"; Cover OD: 24-1/4"; Center Mounting Hole: 1-5/8" (4.13 cm); 3 mounting holes in cover to fasten base of pump to top of cover.
7. Lube Outlet: 3/8" (f) NPT.
8. Pump Tube Length 33-1/2"(85.1 cm) & Center Hole for downtube: OD: 1-1/4"(3.175CM) ID: 1-1/8"(2.86 cm); Overall Height:
9. Solid Cast Pump Handle 13-1/2"(34.3CM) Long x 1"(2.54CM) Diameter for long strokes and pumping leverage. Stroke Length: 2-3/8"(6.1 cm)
10. Output: .28oz/stroke or 11 oz/ min of NLGI#1 @ 80 deg F
11: Original Refinery Container not included.
12. One year Warranty against Defective Materials, Workmanship and Labor
13. All Pumps are Pressure Tested Statically and Dynamically in NLGI#2 Grease for Output, Pressure, Performance and Quality.
14. Replacement and Repair Parts Available.
15. Other Information: Weight and Dimensions:
BOX #1 Pump Assembly: Weight: 15 lbs (6.8 kgs)
BOX DIMS: Length: 6.0"(15.2 cm) X Width:6.5"(16.5 cm) X Height: 45"(114.3cm)
BOX #1: Cover: Weight: 12 lbs (5.4 kgs)
BOX DIMS: Length: 25.0"(63.5 cm) X Width:25.0"(63.5 cm) X Height: 4"(10.2 cm)

Important Note: Follower Plate Not Included





WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: willmarllc@gmail.com
Website: https://www.LubeandJack.com/~wmogrady/Lube.html

"Doing Business with the World"

WILLMARLUBE
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: sales@willmarlube.com
Website: http://www.willmarlube.com