LT508GME

Description: Low Pressure Manual Oil Pump with Cover Assembly for 55 gallon Refinery Container.

1. Includes Low Pressure Manual Oil Pump.

2. 5FT(1.52mts) x 1/2" Low Pressure 300 PSI Oil Delivery Hose.

3. 6" Curved Nozzle Assembly with Non-Drip Nozzle.

4. Optional Attachment: 6" Straight Nozzle Assembly with Non-Drip Nozzle.

5. Output: 1 pint (.473 Liters) per 7 Strokes using SAE90 Gear Lubricant at 70 degrees F OR 1 Liter per 14 Strokes.

6. Lube Outlet: 1/2"NPT(f).

7: Steel Drum Cover Painted in Bright Red . Diameter to fit a standard 400LB (55 Gallon) Refinery Drum; Cover ID: 24" (61 cm); OD: 24-1/4" (61.6 cm); with Cover Center Hole for pump tube: 1-3/4" (4.45 cm); 3 mounting holes to fasten base of pump

8. Pump Tube Length 35-1/8"(89.2 cm) & Outside Diameter 1-5/8"(4.13 cm); Inside Diameter of Tube: 1-1/2" (3.81 cm); Overall Height: closed: 41"(104.1 cm) Open: 54" (137.2 cm) approximately.

9. Solid Cast Pump Handle 16"(40.6 cm) Long x 1"(2.54CM) Diameter for long strokes and pumping leverage. Stroke Length: 3-3/8"(8.57 cm).

10. Original Refinery Container not included.

11. One year Warranty against Defective Materials,

12. All Pumps are Pressure Tested Statically and Dynamically in Gear Lube for Output, Pressure, Performance and Quality.

16. Replacement and Repair Parts Available.

17. Other Information: Weight and Dimensions:

BOX #1: Pump Assembly: Weight: 15 lbs (6.8 kgs).
BOX DIMS: Length: 6.5"(16.5 cm) X Width: 6.5"(16.5 cm) X Height: 45.5"(115.6 cm).
BOX #2: Cover: Weight: 12 lbs (5.4 kgs)
BOX DIMS: Length: 25"(63.5 cm) X Width:25"(63.5 cm) X Height: 4"(50.8 cm)





WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: willmarllc@gmail.com
Website: https://www.LubeandJack.com/~wmogrady/Lube.html

"Doing Business with the World"

WILLMARLUBE
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: sales@willmarlube.com
Website: https://www.willmarlube.com