

LT76600BME

50FT (15.2mtrs) X 3/8" HP GREASE HOSE

DESCRIPTION

50FT (15.2mtrs)x 3/8" High Pressure Grease Hose with
(3/8"NPT(m) X 3/8"NPT(m)) threaded couplings; Used with all
High Pressure Grease Pumps & Equivalents

Hose Type: High Pressure SAE100R2A

Specifications: Inside Diameter: 3/8"; Outside Diameter:
27/32"(11/16")

Thread 3/8" NPT Male

Braid 2 Ply Wire

Maximum Pressure: Working Pressure: 4000PSI (272BAR)

Burst Pressure: 16000PSI (1088 BAR)

Gates Hose: Working Pressure: 4000PSI (272 BAR)

Application: High Pressure Grease Pumps

BOX Weight: 17LBS(7.71KG)

BOX Dimensions: 12" (30.1CM) X 12" (30.1CM) X 4" (10.2cm)



WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: willmarllc@gmail.com

Website: <http://www.iserv.net/~wmogrady/lube.html>



"Doing Business with the World"

WILLMARLUBE

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: sales@willmarlube.com

Website: <http://www.willmarlube.com>