

LT81495ME

High Pressure High Volume Grease Control Valve

DESCRIPTION

Control Valve for Grease(3/8"NPT(f)) w/o flexed extension tube and High Pressure Coupler LT5845ME; For use with all Air Operated High Pressure Grease Pumps; Grease Inlet: 3/8" NPTF; Operating Pressure 7500PSI;

Does not Include 6"(15.24CM) Solid Flexed Extension Tube with 1/8"NPT (m) Thread or zerk coupler LT5845ME

Grease Inlet 3/8" NPT (f)

Repair Kit: R82157ME

For Use with all Air Operated High Pressure Grease Pumps

Can be used with PSI Approved Spring Loaded Grease

Hose Attachment

Complete Repair Kits and Parts Available

Other Information: Weight and Dimensions:

BOX Weight: 2LB(.92KG)

BOX Dimensions: Length: 9.0"(22.9cm) X Width:3-

1/2"(8.9cm) X Height: 1-1/2"(3.8cm)



WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: willmarllc@gmail.com

Website: <http://www.iserv.net/~wmograde/lube.html>



"Doing Business with the World"

WILLMARLUBE

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: sales@willmarlube.com

Website: <http://www.willmarlube.com>