LT82050ME

Description: 120LB(16 Gallon)(54.4KG) Drum Grease Replacement Pump:

1. Includes 50:1 Double Acting High Pressure Pump(LT82050ME) provides uniform pressure and delivery on the up and down stroke

2. Rapid Disconnect Coupler(815ME) & Air Nipple (11660ME)

3. Muffler(LT2601ME)

4. Pump Specifications: Pump Tube Length 27-3/8" (69.5CM) made for 120 lb Drum & 1.0" (2.54CM)Diameter ; Air Motor Height:

11.0"(27.9CM); Overall Height: 38-3/8"(97.47CM) 5. These high pressure Grease Pumps incorporate a 20 cu. in. air

motor design.

6. Output: 80 cu in/minute (45 oz) of Grease at 100PSI NLGI#2 at 70 Degrees ambient temperature (.35 cu in/cycle)

7. Air Inlet 1/8" NPT (f); Lube Outlet: ¼" NPT (f)

8. Additional Accessories Available: LT82103ME Grease Strainer for Pump Tube;

9: New Downtube Packings made of Viton / Teflon for longer life 10. Maximum Air Pressure: 150PSI; Recomended: 80-100PSI;

Maximum Grease Pressure: 7500PSI; Recomended: 5000 PSI; Note: Pump life reduces considerably if operating above the recommended air pressure.

11. One Year Warranty against Defective Materials, Workmanship and Labor

12. All Pumps are Pressure Tested Statically and Dynamically in NLGI#2 Grease at the Factory for Output, Pressure, Performance and Quality.

13: Complete Repair Kits & Parts Available (See Below)

R83054M: Simple Repair Kit for Grease Pumps LT82050ME R83000ME: Air Motor Repair Kit for LT82050ME R83001ME: Down Tube Repair Kit for LT82050ME 14: Other Information: Weight and Dimensions:

Box Weight: 17LBS(7.8KG)

Box Dimensions: Length: 6-1/2"(16.6CM) X Width:6-1/2"(16.6CM) X Height: 49-1/2"(125.8CM)

WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY P.O. BOX 456; ADA, MI. 49301 USA TEL: 616-676-1792; FAX: 616-676-1287 Contact: willmarllc@gmail.com Website: http://www.iserv.net/~wmogrady/lube.html



WILLMARLUBE P.O. BOX 456; ADA, MI. 49301 USA TEL: 616-676-1792; FAX: 616-676-1287 Contact: sales@willmarlube.com Website: http://www.willmarlube.com

