LT82054ME

Description: 400LB(55 Gallon) Drum Grease Replacement Pump: 1. Includes 50:1 Double Acting High Pressure Pump(LT82054ME) provides uniform pressure and delivery on the up and down stroke

- 2. Rapid Disconnect Coupler(815ME) & & Air Nipple (11660ME)
- 3. Muffler(LT2601ME)
- 4. Pump Specifications: Pump Tube Length 33-15/16" (86.20CM) made for 400 lb Drum & 1.0"(2.54CM) Diameter; Air Motor Height:
- 11.0" (27.9CM): Overall Height: 44-15/16"(114.15CM)
- 5. These high pressure Grease Pumps incorporate a 20 cu. in. air motor design.
- 6. Output: 80 cu in/minute (45 oz) of Grease at 100PSI NLGI#2 at 70 Degrees ambient temperature (.35 cu in/cycle)
- 7. Air Inlet 1/8" NPT (f); Lube Outlet: 1/4" NPT (f)
- 8. Additional Accessories Available: LT82103ME Grease Strainer for Pump Tube;
- 9: New Downtube Packings made of Viton / Teflon for longer life
- 10. Maximum Air Pressure: 150PSI; Recomended: 80-100PSI;
- Maximum Grease Pressure: 7500PSI; Recomended: 5000 PSI; Note: Pump life reduces considerably if operating above the recommended air pressure.
- 11. One Year Warranty against Defective Materials, Workmanship and Labor
- 12. All Pumps are Pressure Tested Statically and Dynamically in NLGI#2 Grease at the Facotry for Output, Pressure, Performance and Quality.
- 13: Complete Repair Kits & Parts Available (See Below)

R83054ME: Simple Repair Kit for Grease Pumps LT82054ME R83054M: Complex Repair Kit for Grease Pumps LT82054ME

R83000ME: Air Motor Repair Kit for LT82054ME R83001ME: Down Tube Repair Kit for LT82054ME 14: Other Information: Weight and Dimensions:

BOX Weight: 19LBS(8.62KG)

Box Dimensions: Length: 6-1/2"(16.6CM) X Width:6-1/2"(16.6CM) X

Height: 49-1/2"(125.8CM)



WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY

P.O. BOX 456; ADA, MI. 49301 USA TEL: 616-676-1792; FAX: 616-676-1287 Contact: willmarllc@gmail.com

Website: http://www.iserv.net/~wmogrady/lube.html



WILLMARLUBE

P.O. BOX 456; ADA, MI. 49301 USA TEL: 616-676-1792; FAX: 616-676-1287 Contact: sales@willmarlube.com Website: http://www.willmarlube.com