

LT82398M

Description: 5 Gallon Pail 3:1 Bare Replacment Air Operated Pump for Oil

1. Includes 3:1 Double Acting Low Pressure Pump for Oil (LT82398M)
2. Rapid Disconnect Coupler(815ME)
3. Air Nipple(11660ME); (Extension Tube 10181ME is optional)
4. Muffler(LT2601ME)
5. Comes With or without Threaded Bung Adapter (40045ME) for installation on a pail; Please specify if you require the Bung Bushing.
6. Air Inlet: 1/8" NPT(f);
7. Lubrication Outlet: 3/4" NPT(f)(1.90CM)
8. Pump Tube Diameter: 1-7/8"(4.76CM); Pump Tube Length 12-1/4"(31.1CM); Air Motor Height: 11.0"(27.94cm); Overall Height: 25-1/2"(64.8CM).
9. Output: 4 Gallons/minute (15.1LTRS/MIN)(Free Delivery)
- 10: Recommended Air Pressure 80 to 100 PSI w/ Regulator
11. Replacment Pump made to fit a 5 Gallon Pail.
12. **One Year Warranty against Materials, Workmanship and Labor**
- 13: **Application:** Replacement Pump for a 5 Gallon Pail with a fitting adapter for a screw pump bushing on top.
14. **Additional Accessories Available:**
LT40045ME; Bung Bushing Adapter
LT780ME Gear Oil Control Valve 1/2" NPT(f); Includes:82067ME Shut-Off Valve with built-in Swivel and 82070ME Non-Drip Nozzle Extension. Maximum Operating Pressure 1000PSI.
LT775ME: HD Volume Oil Control Valve 1/2" NPT(f); Includes 82906ME Shut-Off Valve and 82932 Rigid Extension Nozzle; Maximum Operating Pressure 1000PSI.
15. **Complete Repair Kits Available:**
R83071ME: Simple Repair Kit for Oil Pumps LT82398M
R83000ME: Air Motor Repair Kit for LT82398M
16. **Other Information: Weight and Dimensions:**
BOX Weight: 17LBS (7.71KG)
BOX DIM: Length: 14"(35.6cm)XWidth:13"(33.0cm)XHeight: 26"(66.1cm)



WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: willmarllc@gmail.com
Website: <http://www.iserv.net/~wmogrody/lube.html>



"Doing Business with the World"

WILLMARLUBE
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: sales@willmarlube.com
Website: <http://www.willmarlube.com>