

LT84775-1.25ME

Description: Solid Molded Rubber Follower Plate for
Tapered(Conical) Pails

1. Follower Plate Solid Molded Rubber for a 35LB(5 Gallon) (15.9KG)Tapered Pail, & 1-1/4" Diameter Downtube Pumps
2. Center Downtube Diameter Opening 1-1/4"(3.175CM) for a Grease Pump or Equivalent with a 1-1/4"(3.175CM) Diameter Downtube
3. Diameter of Follower Plate: 11-1/4"(28.58CM); Includes a 5/8"(1.59CM) foldable rubber lip around the outer diameter
4. Other Downtube Diameter Inserts available in 1.0" (2.54CM), 1-1/4"(2.50CM), 1-3/8"(3.49CM), 1-1/2" (3.81CM), 2-1/8" (5.4CM). (See Chart Below)
- 5: Provides a tight seal on the other surface of the container for a vacuum suction and better priming in the downtube; forces grease at the bottom of the container from the outer edges toward the center of the pail and the downtube to reduce waste.
6. **Application:** Tapered or Conical Pails/Drums of Grease in a Standard 35LB(5 Gallon) (15.9KG)container or 25LBS(11.3KG) to 50LBS(22.7KG) for 1-1/4" Diameter Downtube Pump or equivalent pump with a Downtube Diameter of: 1-1/4" (3.175CM) (Standard); (See Chart Below)

7. Other Information: Weight and Dimensions:

BOX Weight: 5LBS(2.27KG)

BOX DIMS: Length: 13"(33CM) X Width: 13"(33CM) X Height 3"(7.6CM)



FOLLOWER PLATES WITH LARGER DIAMETER CENTERS

STANDARD: 1.0" Order Model # LT84775ME

OPTIONAL: 1-1/4" Order Model # LT84775-1.25ME

OPTIONAL: 1-3/8" Order Model # LT84775-1.375ME

OPTIONAL: 1-1/2" Order Model # LT84775-1.50ME

OPTIONAL: 2-1/8" Order Model # LT84775-2.125ME

WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: willmarllc@gmail.com

Website: <http://www.iserv.net/~wmogradylube.html>



"Doing Business with the World"

WILLMARLUBE

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: sales@willmarlube.com

Website: <http://www.willmarlube.com>