

LT926-1ME

Description: 400LB(55 Gallon)(181.4KG) Drum Grease Pump

Assembly: Includes: (Unit does not include Drum Cover (LT81523ME))

- 1: 50:1 Double Acting Heavy Duty High Pressure Pump (LT82054ME) provides uniform pressure and delivery on the up and down stroke
- 2: Rapid Disconnect Air Coupler (815ME) & Air Nipple (11660ME) 1/8"(M)
- 3: 3ft (.92mtrs) x 1/4" Air Connecting Hose (LT72036ME)
- 4: 4ft (1.23mtrs) High Pressure Grease Hose(LT75048ME)
- 5: High Pressure Volume Union Elbow 1/4"(F) x 1/4"(M) (82202ME)
- 6: Air Inlet 1/8" NPT (F); Lube Outlet: 1/4" NPT (F)
- 7: Steel Pump Cover (White)(91369ME) & Air Motor Muffler (LT2601ME)
- 8: Pump Specifications: Pump Tube Length 33-15/16" (86.20CM) made for 400 lb Drum & 1.0" (2.54CM)Diameter; Air Motor Height: 11.0"(27.94CM); Overall Height of Unit: 44-15/16"(114.2CM)
- 9: The LT82054ME high pressure Grease Pump incorporates a 20 cu. in. air motor design.
- 10: Output: 80 cu in/minute (45 oz) of Grease at 100PSI NLGI#2 at 70 Degrees ambient temperature (.35cu in/cycle)
- 11: New Downtube Packings made of Viton / Teflon for longer life
12. Maximum Air Pressure: 150PSI; Recomend: 80-100PSI; Maximum Grease Pressure: 7500PSI; Recomend: 5000 PSI; Note: Pump life reduces considerably if operating above the recommended air pressure.
13. **One Year Warranty against Defective Materials, Workmanship and Labor**
14. **All Pumps are Pressure Tested Statically and Dynamically in Grease for performance and output.**
- 15: **Additional Accessories Available:** LT82103ME Grease Strainer for Pump Tube; Follower Plate LT83366ME; Does not include follower plate; must order separately
- 16: **Optional Hoses Available(See Below):**
 - LT75120ME 10ft X 1/4" High Pressure Grease Hose 1/4"(m)
 - LT75240ME 20ft X 1/4" High Pressure Grease Hose 1/4"(m)
 - LT75360ME 30ft X 1/4" High Pressure Grease Hose 1/4"(m)
 - LT75480ME 40ft X 1/4" High Pressure Grease Hose 1/4"(m)
 - LT75600ME 50ft X 1/4" High Pressure Grease Hose 1/4"(m)
 - LT76480BME; 40FT x 3/8" High Pressure Grease Hose 3/8"NPT(m)
 - LT76480AME; 40FT x 1/2" High Pressure Grease Hose 1/2"NPT(m)
 - LT76600BME; 50FT x 3/8" High Pressure Grease Hose 3/8"NPT(m)
 - LT76600AME; 50FT x 1/2" High Pressure Grease Hose 1/2"NPT(m)
- 17: **Complete Repair Kits Available:** LTR83054M: Simple Repair Kit for Grease Pumps 82054ME; LTR83054ME: Complex Repair Kit for Grease Pumps 82054ME; LTR83000ME: Air Motor Repair Kit for 82054ME; LTR83001ME: Down Tube Repair Kit for 82054ME;



18: Other Information : Weights and Dimensions: Weight: 26LB (11.8KG) ; Box Dimensions: (Pump): Length:8"(20.3CM) X Width:11"(27.9CM) X Height: 49-1/2"(125.8CM)

WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: willmarllc@gmail.com

Website: <http://www.iserv.net/~wmograde/lube.html>



"Doing Business with the World"

WILLMARLUBE

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: sales@willmarlube.com

Website: <http://www.willmarlube.com>