

LT987M

Description: Contractor Pump Assembly with Steel Container, Grease Pump Assembly (self enclosed unit) 60LB Bulk or 25Lb to 50 Lb Pails

1. Includes 50:1 Double Acting High Pressure Pump(LT83513ME) provides uniform pressure and delivery on the up and down stroke
- 2 10'(3.1mts) High Pressure Grease Delivery Hose(LT75120ME)
3. High Pressure Grease Delivery Control Valve(LT740ME)
4. Rapid Disconnect Coupler(815ME) & Air Nipple (11660ME) & Air Motor Muffler(LT2601ME)
5. Steel Container Size: 31-3/4"(80.6CM) High by 12-1/2"(31.8CM) Diameter Painted in Red
6. Pump Specifications: Pump Tube Length 18-7/8"(47.9 CM) & Diameter 1.0"(2.54CM); Air Motor height: 11.0"(27.84CM); Overall height of Unit: 29-7/8"(75.8CM);
7. Follower Plate Optional and should be ordered separately.
8. 4 Rigid Steel Clamps that clamp the cover firmly in place on the container
9. Steel Drum Cover with screws that firmly fasten the cover to the base of the pump.
- 10: Cover Gasket and Air Vent in cover assembly makes the unit dust, leak & spill proof
11. Output: 80cu in/minute (45 oz) of grease at 100PSI of NLGI #2 at 70 Degrees ambient Temperature (.35cu in/cycle)
12. Air Inlet 1/8"NPT(f); Lube Outlet: 1/4"NPT(f);
13. These High Pressure Grease Pumps incorporate a 20 cu in Air Motor Design
- 14: **Application:** Construction Sites, Maintenance, where contamination is a major problem and portability is a priority. Excellent in all types of Weather & Dusty Conditions
- 15: New Downtube Packings made of Viton / Teflon for longer life
16. Maximum Air Pressure: 150PSI; Recomend: 80-100PSI; Maximum Grease Pressure: 7500PSI; Recomend: 5000 PSI; Note: Pump life reduces considerably if operating above the recommended air pressure.
17. **One year Warranty against Defective Materials, Workmanship and Labor**
18. **All Pumps are Pressure Tested Statically and Dynamically in NLGI#2 Grease at the Factory for Output, Pressure, Performance and Quality.**
19. **Additional Accessories Available:**LT82103ME Grease Strainer for Pump Tube; LTA5253ME "Z" Swivel for the Control Valve; LT66645ME Locking Swivel 1/4"(m) x 1/4"(f) ;
20. **Optional Hoses Available(See Below):**
LT75120ME 10ft(3.04mtrs) X 1/4" High Pressure Grease Hose w/ 1/4" NPT (male)
LT75240ME 20ft (6.09 mtrs)X 1/4" High Pressure Grease Hose w/ 1/4" NPT (male)
LT75360ME 30ft ((9.14mtrs)X 1/4" High Pressure Grease Hose w/ 1/4" NPT (male)
LT75480ME 40ft (12.2mtrs)X 1/4" High Pressure Grease Hose w/ 1/4" NPT (male)
LT75600ME 50ft (15.2mtrs) X 1/4" High Pressure Grease Hose w/ 1/4" NPT (male)
21. **Complete Repair Kits Parts Available:**
R83054M: Simple Repair Kit for Grease Pumps LT83513ME
R83000ME: Air Motor Repair Kit for LT83513ME
R83001ME: Down Tube Repair Kit for LT83513ME



22: Easy Carry Handles welded to the side of the container for easy transport

23. **Other Information: Weight and Dimensions:**BOX Weight: 40LBS (18.1KG); BOX DIMS: Length: 18"(45.7cm) X Width:16"(40.6cm) X Height: 32"(81.3cm)

WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: willmarllc@gmail.com
Website: <http://www.iserv.net/~wmograde/lube.html>



"Doing Business with the World"

WILLMARLUBE
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
Contact: sales@willmarlube.com
Website: <http://www.willmarlube.com>