

# LT1273DME

**Description: High Pressure Manual Grease Bucket Pump (Bulk Fill Pail Pump) with Steel Container & Follower Plate (self enclosed unit)**

1. Include High Pressure Manual Grease Pump
- 2 5FT(1.52mts) High Pressure Grease Delivery Hose
3. High Pressure Control Valve Handle with 6"(15.24CM) Rigid Extension and Grease Coupler(LT5852ME)
4. Develops a Max Pressure of 3500 LBS(PSI)
5. Lube Outlet: 3/8"(f)NPT
6. Steel Container Size: 16"(40.6CM) High by 9 1/2"(24.1CM) Diameter Painted in Red (Bulk Filled Unit)
7. Pump Tube Length 16.0"(40.6CM) & Diameter 1-1/4"(3.175CM); Overall Height: 25.0"(63.5CM)
8. Follower Plate made of steel that fits the inside of the 9-1/2" (24.13CM) container.
9. 3 Rigid Steel Clamps that clamp the cover firmly in place on the container
10. Steel Drum Cover with screws that firmly fasten the cover to the base of the pump.
- 11: Easy 4-1/4"(10.8CM) Carry Handle welded to the side of the container makes for easy transportability
12. Output: .28oz/stroke or 11 oz/ min of NLGI#1 @ 80 deg F
13. 4"(10.2CM) Welded Foot Support (welded to the base of the container) for additional pumping leverage.
14. 13-1/2"(34.3CM) Long x 1"(2.54CM) Diameter Solid Cast Pump Handle for long strokes and pumping leverage. Stroke Length: 3.0"(7.62CM)
- 15. Two year Warranty against Defective Materials, Workmanship and Labor**
16. Replacement and Repair Parts Available.

**17. Other Information: Weight and Dimensions:**

BOX Weight: 32LBS (9.98KG)

BOX DIMS: Length: 30.5"(77.5cm) X Width:14.5"(36.9cm) X Height: 13"(33.1cm)



**WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY**

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: [willmarllc@gmail.com](mailto:willmarllc@gmail.com)

Website: <http://www.iserv.net/~wmogrady/lube.html>



"Doing Business with the World"

**WILLMARLUBE**

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: [sales@willmarlube.com](mailto:sales@willmarlube.com)

Website: <http://www.willmarlube.com>