

LT82716ME

Description: 35LB(15.9KG) Replacement Grease Pump (also fits 25LB(11.3KG)-50LB(22.7KG) Pails

1. Includes 50:1 Double Acting High Pressure Pump(LT82716ME) provides uniform pressure and delivery on the up and down stroke
2. Rapid Disconnect Coupler(815ME) & Air Nipple (11660ME)
3. Muffler(LT2601ME)
4. Pump Specifications: Pump Tube Length 15-3/4"(40.01cm) & Diameter 1.0"(2.54CM) made for 25LB(11.3KG)-50LB(22.7KG) Pails and Drums; Air Motor Height: 11.0"(27.94CM); Overall Height of Unit: 26-3/4"(67.9CM);
5. These high pressure Grease Pumps incorporate a 20 cu. in. air motor design.
6. Output: 80 cu in/minute (45 oz) of Grease at 100PSI NLGI#2 at 70 Degrees ambient temperature (.35 cu in/cycle)
7. Air Inlet 1/8" NPT (f); Lube Outlet: 1/4" NPT (f)
- 8: New Downtube Packings made of Viton / Teflon for longer life
9. Maximum Air Pressure: 150PSI; Recomend: 80-100PSI; Maximum Grease Pressure: 7500PSI; Recomend: 5000 PSI; Note: Pump life reduces considerably if operating above the recommended air pressure.
10. Additional Accessories Available: LT82103ME Grease Strainer for Pump Tube;
11. **One Year Warranty against Defective Materials, Workmanship and Labor**
12. **All Pumps are Pressure Tested Statically and Dynamically at the factory in NLGI#2 Grease for Output, Pressure, Performance and Quality.**
13. **Complete Repair Kits & Parts Available(See Below).**
R83054M: Simple Repair Kit for Grease Pumps LT82716ME
R83000ME: Air Motor Repair Kit for LT82716ME
R83001ME: Down Tube Repair Kit for LT82716ME
- 14: **Other Information: Weight and Dimensions:**
BOX Weight: 13LBS(5.9KG)
BOX Dimensions: Length: 5-1/2"(13.97CM) X Width:5-1/2" (13.97CM) X Height: 28"(71.12CM)



WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
[Contact: willmarllc@gmail.com](mailto:willmarllc@gmail.com)
[Website: http://www.iserv.net/~wmograzy/lube.html](http://www.iserv.net/~wmograzy/lube.html)



"Doing Business with the World"

WILLMARLUBE
P.O. BOX 456; ADA, MI. 49301 USA
TEL: 616-676-1792; FAX: 616-676-1287
[Contact: sales@willmarlube.com](mailto:sales@willmarlube.com)
[Website: http://www.willmarlube.com](http://www.willmarlube.com)