

LT972ME

Description: *Decorative Portable 50:1 Grease Pump Assembly(35LB or 5 Gallon Pail); w/ Rubber Ringed Follower Plate (also fits 25LB-50LB Pails)(11.3KG-22.6KG)*

1. Includes 50:1 Double Acting High Pressure Pump(83513ME) provides uniform pressure and delivery on the up and down stroke
2. 6'(1.85mts) High Pressure Grease Delivery Hose(LT75072ME)
3. High Pressure Grease Delivery Control Valve(LT740ME)
4. Rapid Disconnect Coupler(815ME) & Air Nipple (11660ME) & Air Motor Muffler(LT2601ME)
6. Pump Specifications: Pump Tube Length 18-7/8"(47.94CM) & DIA 1.0"(2.54CM) made for 25-50 lb Pails and Drums; Air Motor Height: 11.0"(27.94CM); Overall Height of Unit: 28-7/8"(73.34CM)
7. Follower Plate (LT91500ME) w/ Rubber Outer Wiping Ring for Conical Pails; (1.0"(2.54CM) Diameter) assures positive prime and vacuum at low temps (prevents cavitation)
8. Other Follower Plates Available: LT84775ME Molded Rubber Follower Plate (Diameter 1.0"(2.54CM)); LT91500M: Solid Steel Follower Plate (Diameter 1.0"(2.54CM))
9. Air Motor Cover in White (91407ME)
10. Steel Drum Cover riveted to the decorative sheet metal cannister; Cover Diameter: 15-1/8"(38.42CM) Opening (Downtube Diameter Opening 2-1/4") w/ 4 mounting holes to attach base of pump to the cover.
- 11: White Metal Cannister measuring 18.0"(45.72CM) x 15-1/8"(38.42CM)
12. Roll-a-Round Base with 4 Heavy Duty Rubber Swivel Casters (2-1/2"(5.72CM) x 3/4"(1.91CM)) for easy maneuverability(LT81319ME)
13. Output: 80cu in/minute (45 oz) of grease at 100PSI of NLGI #2 at 70 Degrees ambient Temperature (.35cu in/cycle)
- 14: New Downtube Packings made of Viton / Teflon for longer life
15. Air Inlet 1/8"NPT(f); Lube Outlet: 1/4"NPT(f);
16. These High Pressure Grease Pumps incorporate a 20 cu in Air Motor Design .
17. Maximum Air Pressure: 150PSI; Recommended: 80-100PSI; Maximum Grease Pressure: 7500PSI; Recommended: 5000 PSI; Note: Pump life reduces considerably if operating above the recommended air pressure.
18. **One Year Warranty against Defective Materials, Workmanship and Labor**
19. **All Pumps are Pressure Tested Statically and Dynamically in NLGI#2 Grease at the Factory for Output, Pressure, Performance and Quality.**
20. **Additional Accessories Available:** LT82103ME Grease Strainer for Pump Tube; LTA5253ME "Z" Swivel for the Control Valve; LT66645ME Locking Swivel 1/4"(m) x 1/4"(f) ;
21. **Optional Hoses Available(See Below):**
LT75120ME 10ft(3.04mtrs) X 1/4" High Pressure Grease Hose
LT75240ME 20ft (6.09 mtrs)X 1/4" High Pressure Grease Hose
LT75360ME 30ft ((9.14mtrs)X 1/4" High Pressure Grease Hose
LT75480ME 40ft (12.2mtrs)X 1/4" High Pressure Grease Hose
LT75600ME 50ft (15.2mtrs) X 1/4" High Pressure Grease Hose



22. Complete Repair Kits & Parts Available:

R83054M: Simple Repair Kit for Grease Pump LT83513ME

R83000ME: Air Motor Repair Kit for Pump LT83513ME

R83001ME: Down Tube Repair Kit for Pump LT83513ME

23. Other Information: Weight and Dimensions:

BOX Weight: 55LBS (24.95KG)

BOX DIMS: Length: 20.5"(52.07CM) X Width:20.5"(52.07CM) X Height: 34.5"(87.63CM)

WILLMAR INTERNATIONAL LLC / LUBE TECHNOLOGY

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: willmarllc@gmail.com

Website: <http://www.iserv.net/~wmogradylube.html>



"Doing Business with the World"

WILLMARLUBE

P.O. BOX 456; ADA, MI. 49301 USA

TEL: 616-676-1792; FAX: 616-676-1287

Contact: sales@willmarlube.com

Website: <http://www.willmarlube.com>